


LSI7104EP/LSI7204EP/LSI7404EP

4Gb Fibre Channel Adapter Series



4Gb FC PCI Express Adapter Series Offers Faster Server to San Connectivity and Improved Data Protection

KEY ADVANTAGES

- Intel/AMD/SPARC Servers
- SAN switch or JBOD (disk) attach
- Storage backup and recovery
- Storage virtualization appliance
- Digital video networks
- Tiered storage application

FEATURES

- Available one, two or four ports
 - All ports, 800MB/s per port in full-duplex mode
- Auto-speed (1, 2, and 4Gb/s)
 - Includes SFP optics
- MyStorage™ Management allows centralized management and remote control
- PCI Express x8 lanes
- Over 200,000 I/Os per second
- Link speed/activity LED(s)
- End-to-end data integrity (T10 DIF support)
- FCP-2 tape support
- Persistent binding, LUN masking
- Loopback and read/write buffer tests
- SCSI initiator, target and initiator/target modes with support of 126 alias ALPA
- Connect directly to RAID, Disk or Switch equipment
- ARM® CPUs for FC offload
- Supports bootable devices
- All Major OS drivers
- Fusion-MPT™ compliant single and dual channel has low profile bracket options
- 3 year limited warranty RoHS compliance

LSI Delivers Unsurpassed Performance

Our 4Gb/s Fibre Channel PCI Express adapter series fulfills virtually any storage connection need or environment, whether data mining, video and media streaming, or high availability. These adapters were engineered to deliver unequalled performance, high port density, easy installation, as well as accommodating PCI Express host platforms.

Guards Past Investments While Providing Advanced Data Protection

Each adapter features full-duplex capable FC ports, that automatically detect connection speed, and can each independently operate at 1, 2 or 4Gb/s. The ability to operate at slower speeds ensures that these adapters remain fully compatible with legacy equipment. All adapters also support new end-to-end error detection (CRC) for improved data integrity when reading or writing disks. The AN SIT10 committee developed and endorses this new protection standard.

MyStorage Management Software

MyStorage Management Software is a host software package designed to simplify management of LSI Fibre Channel adapters. New users will appreciate the simple, threeclick installation and its “auto-everything” intelligence. Advanced users will find the utility provides all the features to finetune the adapter operation for specific applications in even the most complex SAN environments. MyStorage software is prefigured with ease of use in mind, whether you’re deploying a simple SAN for mid-range applications or a more complex enterprise data center.

Fusion-MPT Architecture

These Fibre Channel host adapters use LSI’s powerful FC949E controller, which implements the Fusion-MPT (Message Passing Technology) architecture. Each controller features multiple, embedded ARM® processors that deliver maximum host CPU offload. The built-in intelligence enables LSI to publish a single OS driver to operate any Fusion-MPT controller or adapter. Fusion-MPT enables LSI to quickly offer new adapters with a rich compliment of OS drivers, each with proven track records and years of successful run time.

LSI7104EP/LSI7204EP/LSI7404EP 4GB FIBRE CHANNEL ADAPTER SERIES			
ADAPTER MODEL	LSI7104EP-LC	LSI7204EP-LC	LSI7404EP-LC
External Port Quality	Single (x1)	Dual (x2)	Quad (x4)
External Connector(s)	Fibre Channel LC style Pluggable (SFP), multimode optics (850nm)		
LED Indicators (per Port)	1 tricolor speed: Blue = 4G, Green + 2G, Amber = 1G		
Data Transfer Rates	Full duplex 800MB @ 4Gb, (400MB @ 2Gb, 200MB @ 1Gb)		
Supported Architectures	x86, IA64, SPARC, AMD64, EM64T		
Host Bus Type	Native PCI Express x8 host bus interface		
Operating Voltage	3.3V operation		
Power Consumption	<9.0 Watts	<9.0 Watts	<18 Watts
Protocols	SCSI-FCP, FCP2, FC-tape		
Topology	Point-to-point, arbitrated loop, switched fabric (N_port, NL_port, FL_port, F_port)		
Class of Service	Class 2 Ack 0 and Class 3		
ANSI FC Standards	FC-PH, FC-AL2, FC-FCP, FC-PLDA, FC-FLA, FC-tape		
Agency Certification	CE, VCCI, Canada, C-tick, FCC class A, UL 94VO		
Size	Low profile, 6.6" x 2.714"	Low profile, 6.6" x 2.714"	Full height 6.6" x 4.376"
SOFTWARE			
MyStorage	Exceptionally easy to use and comprehensive HBA configuration and management (available on Windows and Linux platforms)		
OS Driver Support	<ul style="list-style-type: none"> • Windows Server 2003 (includes STORport and SCSIport), Window 2000, Windows XP • SCO OpenServer 5.x • Solaris 8x86, Version 2.8 through 10 • Solaris SPARC, Version 2.6 through 10 • UnixWare 7.x • Linux RedHat (Intel x86, Intel Itanium, Intel EM64T, AMD64): RHEL 2.0, 3.0, 4.0, 5.0 • Linux SuSE (Intel x86 Intel Itanium, Intel EM64T, AMD64): SLES 8.0, 9.0, 10.0 • Linux Fedora Professional • FreeBSD 		
ENVIRONMENTAL CONDITIONS			
Operating Temperature	0°C to 55°C (dry bulb)		
Storage Temperature	-40°C to 105°C (dry bulb)		
Relative Humidity	5% to 90% non-condensing		
Max Dew Point	32°C		
Warranty	3 years, advanced replacement option, free advanced technical support at www.lsi.com/support		

Warranty

For more than 15 years, LSI host adapters have been providing high-performance SCSI solutions to leading server, disk array and computer systems worldwide. Each host adapter carries a powerful chip built in LSI Logic's ISO 9001-certified fabrication facilities. Using only the highest quality components, LSI host adapters are assembled and tested in world-class facilities to assure superior product reliability and performance. Because of stringent quality management programs, our host adapters carry a three-year limited warranty.



For more information and sales office locations, please visit the LSI web sites at: lsi.com lsi.com/contacts

North American Headquarters
Milpitas, CA
T: +1.866.574.5741 (within U.S.)
T: +1.408.954.3108 (outside U.S.)

LSI Europe Ltd.
European Headquarters
United Kingdom
T: [+44] 1344.413200

LSI KK Headquarters
Tokyo, Japan
Tel: [+81] 3.5463.7165

LSI, the LSI logo design, Fusion-MPT and MyStorage are trademarks or registered trademarks of LSI Corporation. All other brand and product names may be trademarks of their respective companies.

LSI Corporation reserves the right to make changes to any products and services herein at any time without notice. LSI does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by LSI; nor does the purchase, lease, or use of a product or service from LSI convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual property rights of LSI or of third parties.

Copyright ©2007 by LSI Corporation. All rights reserved. 1007 10038

