



connect • monitor • manage

FUJITSU

EMULEX®

CONNECT - DATA SHEET

OCe14102-NX-F Dual-port 10Gb Ethernet Network Adapters

For Fujitsu servers

High Performance Networking for Enterprise Virtualization and the Cloud



OneConnect OCe14102-NX-F

Overview

As the fourth generation of the Emulex OneConnect® product line, the OCe14102-NX-F Ethernet network adapter provides high performance 10Gb Ethernet (10GbE) connectivity delivering multiple benefits for the enterprise cloud, including:

- Increasing data center IT agility and scalability through deployment of a secure multi-tenant cloud
- Optimizing server hardware utilization by scaling high density virtualization
- Delivering user-controlled bandwidth partitioning across workloads and management services

The OCe14102-NX-F 10GbE network adapter is designed for the high bandwidth and scalability demands of enterprise applications, more scalable virtualization with support for RDMA traffic over Converged Ethernet (RoCE) fabric, enhanced Single-Root I/O Virtualization (SR-IOV) and NIC port partitioning, and next generation overlay network technologies that address the requirements virtual machine (VM) mobility and massive scaling of Layer 2 subnets inside private or hybrid cloud infrastructures.

Emulex Virtual Network Exelation (VNeX™) overlay network offloads for multi-tenant cloud networking

Scaling existing technologies for private or public multi-tenant infrastructures requires networking solutions that can enable VM-to-VM communication and virtual workload migration across Layer 2 and Layer 3 boundaries without impacting connectivity or performance.

At the same time, these solutions need to ensure isolation and security for thousands or millions of tenant networks. However, with existing technology, the available 4094 VLAN IDs are insufficient to isolate/secure each tenant in a data center (private cloud) or hybrid cloud environment.

Virtual Extensible Local Area Network (VXLAN), supported by VMware, and Network Virtualization using Generic Routing Encapsulation (NVGRE), supported by Microsoft, are next-generation overlay networking solutions that address these requirements. These solutions are a frame-in-frame data packet encapsulation scheme enabling the creation of virtualized Layer 2 subnets that can span physical L3 IP networks. Traffic from each VM is tunneled to a specific virtual network; the packets are then routed transparently over the existing physical infrastructure.

Emulex VNeX offload technology powered by a multi-core adapter ASIC engine accelerates the performance of network virtualization by preserving legacy stateless TCP offloads and scaling methods on encapsulated packets, providing full native network performance in a virtual network environment.

Key benefits

- Maximizes server hardware ROI with high virtual machine density
- Simplifies deployment of secure, scalable multi-tenant cloud infrastructures
- Accelerates applications performance
- Provides the bandwidth needed for slot constrained server platforms
- Reduces complexity through the deployment of a common network platform
- Reduces management, infrastructure and energy costs



OneConnect®



OneCommand®

OCe14102-NX-F Dual-port 10Gb Ethernet Network Adapters

RDMA support

The OCe14102-NX-F adapters leverage RoCE enabling server to server data movement directly between application memory without any CPU involvement providing high throughput and data acceleration on a standard Ethernet fabric without the need for any specialized infrastructure or management.

Optimized host virtualization density with SR-IOV support

SR-IOV optimizes I/O for VMs, enabling higher host server virtualization ratios to deliver maximum server ROI. SR-IOV provides a more cost-effective solution than multiple, physical adapter ports. SR-IOV enables multiple VMs to directly access the OCe14102-NX-F's I/O resources, thus allowing VM networking I/O to bypass the host and take a path directly between the VM and the adapter, eliminating redundant I/O processing in the hypervisor. This, in turn, allows higher I/O performance, lower CPU utilization and significantly reduced latency as compared to the alternative of software-emulated NIC devices that are implemented in the hypervisor.

Optimized bandwidth allocation with Emulex Universal Multi-Channel port partitioning

Emulex Universal Multi-Channel (UMC) is ideal for virtualized server environments because bandwidth allocation can be optimized to support virtual machine migration, management and I/O intensive applications. UMC allows multiple PCI physical functions to be created on each adapter port. Each port on the OCe14102-NX-F can be configured with up to sixteen functions.

Simplified management with Emulex OneCommand® Manager application

The Emulex OneCommand Manager application provides centralized management of Emulex OneConnect CNAs and LightPulse® HBAs throughout the data center from a single management console. The OneCommand Manager application provides a graphical user interface (GUI) and a scriptable command line user interface (CLI). Emulex OneCommand Manager for VMware is fully integrated with VMware vCenter to simplify management for virtual server deployments.

Fourth generation platform delivers enterprise-class reliability and performance

Leveraging generations of advanced, field-proven controller and adapter technology, OCe14102-NX-F adapters meet the robust interoperability and reliability requirements of enterprise and scale-out data centers.

Key features

- Superior network scalability—10GbE bandwidth on common software platform
- SR-IOV
- Data acceleration with RoCE support
- Powerful hardware offload for:
 - Overlay networks (NVGRE and VXLAN)
 - Stateless TCP
- Greater bandwidth with PCIe 3.0
- VMware vSphere NetQueue support
- Microsoft Windows Server VMQ and Dynamic VMQ support

OCe14102-NX-F Dual-port 10Gb Ethernet Network Adapters

Controller

- Skyhawk
(Emulex Engine, XE100 series controllers)

Ethernet standards

- Single IEEE 802.3ba 40GBASE Ethernet port (40GBASE-SR4/40GBASE-CR4)
- Single or Dual IEEE 802.3-2008 10GBASE Ethernet ports (10GBASE-SR/10GBASE-LR/10GBASE-CR)
- Single or dual 1GBaseX/SGMII auto negotiation
- IEEE 802.1Q virtual LANs (VLAN)
- IEEE 802.3x Flow control with Pause frames
- IEEE 802.1Qbg Edge Virtual Bridging
- IEEE 802.1Qaz Enhanced Transmission Selection (ETS); Data Center Bridging Capability Exchange (DCBX)
- IEEE 802.1Qbb Priority Flow Control (PFC)
- IEEE 802.3ad Link Aggregation/LACP
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

Ethernet network interface (Layer 2 NIC) and TCP/IP

- NDIS 6.0, 6.2, 6.3-compliant Ethernet functionality
- IPv4/IPv6 TCP, UDP checksum offload
- IPv4/IPv6 Receive Side Scaling (RSS)
- IPv4/IPv6 Large Receive Offload (LRO)
- IPv4/IPv6 Large Send Offload (LSO)
- Dynamic VMQ (Windows Server 2012 Hyper-V and NetQueue (VMware vSphere))
- Programmable MAC and VLAN addresses
- 128 MAC/VLAN addresses per port
- Support for hash-based Multicast MAC address filters
- Support for hash-based Broadcast frame filters per port
- VLAN offloads (insertion and extraction)
- Jumbo frame support up to 9000 Bytes

I/O virtualization

- Stateless L2, L3, and L4 offloads for frame-in-frame encapsulation (VXLAN, NVGRE)
- PCI-SIG Address Translation Service (ATS) v1.0
- Support for up to 512 hardware queues
- Virtual Switch Port Mirroring for diagnostic purposes
- Virtual Ethernet Bridging (VEB)
- Virtual Ethernet Port Aggregator (VEPA)
- OneConnect Universal Multi-Channel™ (UMC), support for up to 16 PCIe physical functions (PFs) per adapter which can be used as partitions as follows:
 - OCe14401 Ethernet adapter, the port can support 16 NIC functions
 - OCe14101 or OCe14102 Ethernet adapters, each port can support eight NIC functions
 - Note: the system hardware must support and enable ARI and the host operating system must support ARI for maximum number of functions to be enabled; see Emulex UMC manual for more details
- NIC Single Root I/O Virtualization (SR-IOV)
 - up to 63 virtual functions (VFs) per port
- QoS for controlling and monitoring bandwidth assigned to and used by virtual entities
- Configurable control of network bandwidth by physical port, queue, or protocol
- Traffic shaping and QoS across each VF and PF

Converged Enhanced Ethernet (CEE) and Datacenter Bridging (DCB)

- IEEE 802.1Qbb Priority Flow Control (PFC)
- IEEE 802.1Qaz Enhanced Transmission Selection (ETS)
- IEEE 802.1Qaz Data Center Bridging Exchange (DCBX)
- Absolute per-priority rate control option/ configuration

Remote Direct Memory Access (RDMA)

- Direct data placement in application buffers without CPU intervention
- Supports IBTA RoCE specifications
- Linux Open Fabrics Enterprise Distribution (OFED) support
- Low latency queues for small packet sends and receives
- Windows Server SMB Direct (SMB over RDMA)

PCI Express (PCIe) interface

- PCIe 3.0 x8 (8, 5.0, and 2.5 GT/s per lane) compliant interface:
 - Up to 64 Gb/s full duplex bandwidth
 - Configurable width and speed to optimize power versus bandwidth
- Support for up to 16 PCIe physical functions (PFs)
- Support for x1, x2, x4, and x8 links widths
- NIC Single Root I/O Virtualization (SR-IOV)
 - up to 63 virtual functions (VFs) per port
- Message Signal Interrupts (MSI-X)
- Advanced Error Reporting (AER)
- Completion Timeout (CTO)
- Function Level Reset (FLR)
- Alternative Routing ID Interpretation (ARI)

Comprehensive OS support

- Windows
- Red Hat Enterprise Linux
- SUSE® Linux Enterprise Server
- Oracle Linux
- VMware vSphere
- CentOS
- Debian
- Ubuntu
- FreeBSD
- CITRIX XENServer

Management, boot support

- vCenter management plugin support
- Role-based management, integrated with Active Directory and LDAP
- Multi-channel configuration and bandwidth control
- UEFI and x86 remote boot support including PXE v2.1, UEFI 2.3.1
- MAC statistics gathering (SNMP, Ethernet MIB, MIB2, RMON, RMON2)
- Offline and online firmware updates
- Integrated thermal sensor works with management utilities

Hardware environments

- Fujitsu x86, x64 servers

Please refer to the product page on www.emulex.com for further details.

OCe14102-NX-F Dual-port 10Gb Ethernet Network Adapters

Interconnect

Copper

- SFP+ Direct Attached Twin-Ax Copper interface
- Standards compliant passive copper cables up to 5m and active copper cables up to 10m

Optical

- Optic 10GBASE-SR short wave lasers with LC type connector supported up to 300m on laser-optimized OM3 multimode fiber (MMF) cables
- Optic 10GBASE-LR long wave lasers with LC type connector supported up to 10Km single mode fiber (SMF) cable, Ethernet use only

Physical dimensions

- Short, low profile MD2 form factor card
- 167.64mm x 68.91mm (6.60" x 2.71")
- Standard, full height bracket installed (low-profile bracket available)

Environmental requirements

- Operating temperature: 0° to 55°C (32° to 131°F)
- Storage temperature: -40° to 70°C (-40° to 158°F)
- Relative humidity: 5% to 95% non-condensing

Agency and product safety approvals

North America

- FCC/Industry Canada Class A
- UL/CSA Recognized
- Class 1 Laser Product per DHHS 21CFR (J)

Europe

- CE Mark
- EU RoHS compliant
- TUV Bauart Certified
- Class 1 Laser Product per EN60825-1

Australia

- C-Tick Mark

Japan

- VCCI Class A

Taiwan

- BSMI Class A

Korea

- MSIP (formally KCC/MIC) Class A

China

- China RoHS Compliant

Ordering information

Please refer to Fujitsu website for product ordering:
<http://docs.ts.fujitsu.com/dl.aspx?id=eba2c160-53e0-4aac-b526-149f84f12bfd>



World Headquarters 3333 Susan Street, Costa Mesa, CA 92626 +1 714 662 5600
 Bangalore, India +91 80 40156789 | Beijing, China +86 10 84400221
 Dublin, Ireland +35 3 (0) 1 652 1700 | Munich, Germany +49 (0) 89 97007 177
 Paris, France +33 (0) 158 580 022 | Tokyo, Japan +81 3 5325 3261 | Singapore +65 6866 3768
 Wokingham, United Kingdom +44 (0) 118 977 2929 | Brazil +55 11 3443 7735

www.emulex.com