

Generations Ahead

Unparalleled manageability, reliability, performance and ease of deployment

Streamlined installation and management, unrivaled scalability, and industry-leading virtualization support make the Emulex LP1105-BU dual-channel mezzanine card an ideal solution for systems using the Intel[®] Blade Server Chassis environments.



Proven design, architecture and interface

LightPulse HBAs' highly integrated single-chip design minimizes onboard components, while advanced error-checking methods assure robust data integrity. The Emulex firmware-based architecture enables feature and performance upgrades without costly hardware changes. The unique Service Level Interface (SLI[™]) allows use of a common driver across all models of Emulex HBAs. Installation and management applications are designed to minimize reboots and further simplify deployment.

4Gb/s FIBRE CHANNEL

Expansion Card Host Bus Adapter
for the Intel Blade Server Chassis

KEY BENEFITS

- ⦿ Superior quality and reliability ensure data availability
- ⦿ Highly efficient installation accelerates deployment and reduces administration costs
- ⦿ Maximum SAN performance increases scalability and user satisfaction in large enterprise installations
- ⦿ Robust interoperability simplifies deployment and upgrades of SAN hardware and software
- ⦿ LightPulse Virtual HBA technology provides efficient host utilization and compliance with SAN management best practices
- ⦿ Advanced security protects the SAN from potential threats such as WWN spoofing, host masquerading, rogue/compromised servers and administrator errors

KEY FEATURES

- ⦿ Exceptional performance and full-duplex data throughput
- ⦿ Comprehensive virtualization capabilities with support for N-Port ID Virtualization (NPIV) and Virtual Fabric
- ⦿ Simplified installation and configuration using common HBA drivers and AutoPilot Installer[®]
- ⦿ Efficient administration via HBAnyware[®] for HBAs anywhere in the SAN
- ⦿ Common driver model eases management and enables upgrades independent of HBA firmware

Specifications

STANDARDS

ANSI Fibre Channel: FC-PH-3, FC-PI-2, FC-FS, FC-AL-2, FC-GS-4, FC-FLA, FC-PLDA, FC-TAPE, FCP-2, and RFC 2625 (IP over FC)

PCI-X 1.0a and PCI 3.0

Fibre Channel class 2 and 3

ARCHITECTURE

Dual-channel

4Gb/s, 2Gb/s or 1Gb/s FC Link speeds automatically detected

Integrated data buffer and code space memory

COMPREHENSIVE OS SUPPORT

Windows Server 2003

Windows 2000

Linux

VMware

HARDWARE ENVIRONMENTS

Bull NovaScale Blade Server

Intel Blade Server Platforms

POWER AND ENVIRONMENTAL REQUIREMENTS

Volts: +3.3 and 5 VDC

Operating temperature: 0° to 52°C (32° to 126°F)

Airflow required: 400 lf/m

Storage temperature: -40° to 70°C (-40° to 158°F)

Relative humidity: 5% to 95% non-condensing

ORDERING INFORMATION

Order Part Number: LP1105-BU

ADDITIONAL FEATURES

Emulex LightPulse technology features Frame-level Multiplexing and out-of-order frame reassembly for maximum link utilization.

End-to-end data protection with hardware parity, CRC, ECC and other advanced error checking ensure that data is safe from corruption.

Detailed real-time event logging and tracing enable quick diagnosis of SAN problems.

Universal Boot capability allows the appropriate boot environment to be automatically selected for any given OS.

SOFTWARE FEATURES

Emulex's feature-rich software simplifies and speeds deployment and device management, while reducing administration costs and protecting your IT investment.

HBAnyware enables centralized discovery, monitoring, reporting and management of both local and remote HBAs from a secure remote client. HBAnyware provides in-depth management capabilities including remote firmware and boot code upgrades, statistics and advanced diagnostics. An extensive CLI is available for scripting.

AutoPilot Installer simplifies the installation and configuration of drivers and management applications for multiple HBAs on Windows servers. A single installation of drivers and applications eliminates multiple reboots and ensures that each component is installed correctly and the HBA is ready to use.



This document refers to various companies and products by their trade names. In most, if not all cases, their respective companies claim these designations as trademarks or registered trademarks. This information is provided for reference only. Although this information is believed to be accurate and reliable at the time of publication, Emulex assumes no responsibility for errors or omissions. Emulex reserves the right to make changes or corrections without notice.

08-033revC 10/13