

# Emulex<sup>®</sup> OneCommand<sup>®</sup> Manager Application for Windows

Release 12.0.261.13-1

---

## Purpose and Contact Information

These release notes describe the supported operating systems, new features, resolved issues, known issues, and technical tips associated with this release of the Emulex<sup>®</sup> OneCommand<sup>®</sup> Manager application for Windows.

For the latest product documentation, and for supported driver versions, go to [www.broadcom.com](http://www.broadcom.com). If you have questions or require additional information, contact an authorized Broadcom<sup>®</sup> Technical Support representative at [ecd-tech.support@broadcom.com](mailto:ecd-tech.support@broadcom.com).

## Supported Operating Systems

- Windows Server 2019
- Windows Server 2016
- Windows Server 2012 and Windows Server 2012 R2 (x64 versions, Enterprise, and Server Core installation)
- Windows 10
- Windows 8-x64 (Base version, Pro, and Enterprise)

## New Features

- Adds support for Windows Server 2019.
- Adds support for LPe35000-series adapters.

**NOTE:** Do not use a driver earlier than the drivers documented in these release notes with LPe35000-series adapters.

## Resolved Issues

There are no resolved issues in this release.

## Known Issues

- If you use the OneCommand Manager application on the Windows operating system to manage adapters installed on the ESXi 6.7 Update 1 operating system, the features listed in [Table 1](#) are unavailable.

**Table 1: Unavailable Features**

Feature Description	GUI Element	CLI Command
Set port speed	<b>Firmware Parameters</b> tab (for non-LPe12000 adapters). For LPe12000-series adapters, the port speed is configured with a driver parameter that is available.	SetPortSpeed
Enable or disable a port	<b>Port Information</b> tab	SetPortEnabled
Enable or disable boot code	<b>Boot from SAN Configuration</b> dialog	EnableBootCode
Run diagnostics tests	<b>Diagnostics</b> tab	Only the following Diagnostic commands: <ul style="list-style-type: none"> <li>■ DPortTest</li> <li>■ EchoTes</li> <li>■ FcTraceRoute</li> <li>■ GetBeacon</li> <li>■ LoadList</li> <li>■ LoopBackTest</li> <li>■ LoopMap</li> <li>■ PostTest</li> <li>■ SetBeacon</li> <li>■ Wakeup</li> </ul>
WWN management	<b>Maintenance</b> tab	ChangeWWN GetWWNCap ReadWWN RestoreWWN
Create and delete diagnostic dump files	<b>Diagnostics</b> tab (LPe12000-series adapters) <b>Firmware</b> tab (all other adapters)	Dump commands
Get IPL file name	<b>Adapter Information</b> tab	HbaAttributes
Firmware download	<b>Maintenance</b> tab (LPe12000-series adapters) <b>Firmware</b> tab (all other adapters)	Download
Firmware parameters	<b>Firmware Parameters</b> tab	getfwparams setfwparam

The features listed in [Table 2](#) are available using the OneCommand Manager application on the Windows operating system to manage adapters installed on the ESXi 6.7 Update 1 operating system.

**Table 2: Available Features**

Feature Description	GUI Element	CLI Command
Perform discovery	<b>Discovery Information</b> tab	ListHBAs
View adapter information	<b>Adapter Information</b> tab	HbaAttributes
View port information	<b>Port Information</b> tab	PortAttributes
View port statistics	<b>Statistics</b> tab	PortStatistics
View server attributes	N/A	ServerAttributes

**Table 2: Available Features (Continued)**

Feature Description	GUI Element	CLI Command
Configure driver parameters	<b>Host Driver Parameters</b> tab <b>Driver Parameters</b> tab	DriverConfig GetDriverParams GetDriverParamsGlobal SaveConfig SetDriverParam SetDriverParamDefaults
View transceiver information	<b>Transceiver Data</b> tab	GetXcvrData
View PCI register information	<b>Diagnostics</b> tab	PciData

**Workaround**

Use the esxcli management tool or the OneCommand Manager for VMware vCenter application to manage adapters installed on the ESXi 6.7 Update 1 operating system.

- The fFiber Optic Interconnect Technology (FOIT) AFCT-57F3TMZ-ELX (16GFC longwave optic transceiver) does not support D\_Port (also called ClearLink<sup>®</sup>) for Brocade<sup>®</sup> switches and MDS Diagnostic for Cisco switches.
- Beginning with software release 11.2, FC HBAs and OneConnect<sup>®</sup> converged network adapters (CNAs) have independent software kits. Before updating earlier drivers and applications to the software in release 12.0.3, refer to the *Emulex Software Kit Migration User Guide* for special instructions and considerations for using the 11.2 and later software kits for FC HBAs and OneConnect CNAs.
- The OneCommand Manager application does not display updated driver parameters after a batch update. ([BZ 196979](#)/[BZ 204040 Feature may be removed in RT 12.4](#))

**Workaround**

None.

- Disabling ExpressLane™ on all LUNs attached to a vPort discovered using the CIM interface fails. ([BZ 209163](#)/[BZ 209165 Keep. Release noted](#))

**Workaround**

Disable ExpressLane on individual LUNs attached to the vPort.

- Enabling ExpressLane on LUNs assigned to vPorts with nonzero LUN IDs results in an error. ([BZ 215052](#)/[BZ 216602 works as designed](#))

**Workaround**

None.

- Enabling and disabling Fabric Assigned Port World Wide Name (FA-PWWN) might cause an adapter port's WWPN to change. The OneCommand Manager application discovery-tree might not display the port's newly assigned WWPN. ([QC 10292](#)/[BZ 216549](#))

**Workaround**

Stop and restart the OneCommand Manager application services and daemons when prompted by the OneCommand Manager application.

- Windows driver parameters do not persist after a reboot if they are set with FA-PWWN enabled. ([BZ 207763 keep](#)/[BZ 208101 keep. Release noted](#))

**Workaround**

Perform the following steps:

- a. Disable FA-PWWN.
  - b. Reset the port.
  - c. Change the driver parameters, using the OneCommand Manager GUI.
  - d. Enable FA-PWWN.
  - e. Reboot the system.
  - f. Reconfigure the driver parameters.
  - g. Verify that the correct driver parameters are used.
9. The **Target Mapping** tab allows you to create duplicate target bindings with different bus and target IDs. The first target binding is used after a reboot. ([BZ 212599](#))

**Workaround**

You can change target bindings using the **Target Mapping** tab.

10. The message `WWN Management is disabled while FA-PWWN is enabled` is sometimes displayed when FA-PWWN is not enabled. ([BZ 213420](#))

**Workaround**

None.

11. The **Target Mapping** tab allows you to create duplicate target bindings with different SCSI and bus IDs. ([BZ 212599 new](#))

**Workaround**

Use the **Target Mapping** tab to change incorrect settings.

12. Except on LPe12000-series HBAs, resetting or disabling HBA ports turns off beaconing. ([BZ 218488](#))

**Workaround**

Enable beaconing after resetting or disabling HBA ports.

## Technical Tips

1. If you change the volatile World Wide Name (WWN) on an LPe16000-series adapter, a reboot is required. ([BZ 139520 Keep](#))
2. OneCommand Manager CLI commands might fail in Windows PowerShell. ([BZ 160451 Keep](#))  
OneCommand Manager CLI commands with parameters that contain embedded commas, such as `SetDCBPriority`, fail execution in Windows PowerShell.  
**Workaround**  
Enclose embedded commas in quotation marks. For example, the following command:  
`hbacmd SetDCBPriority 10:00:00:00:c9:3c:f7:88 3 0,1,2,4,5,6,7 3 0 0 0 0 0 0`  
must be formatted as follows to run successfully in Windows PowerShell:  
`hbacmd SetDCBPriority 10:00:00:00:c9:3c:f7:88 3 "0,1,2,4,5,6,7" 3 0 0 0 0 0 0`
3. If a switch-connected port speed is configured to Auto-negotiate and the adapter port speed is also configured to Auto-negotiate (the default), the **Port Information** tab displays **8 Gb/s** as the port speed. If the speed of the adapter is changed without the OneCommand Manager application GUI, the port speed does not change on the **Port Information** tab. ([BZ 152875 Keep](#))

**Workaround**

When possible, use the OneCommand Manager application GUI to change the port speed of the adapter.

4. Start a command shell with the Run As Administrator option for OneCommand Manager CLI commands and batch files, if User Account Control (UAC) is enabled.

If you do not start the command shell with the Run as Administrator option, Windows shows a dialog that prompts you to allow UAC. After you agree to allow UAC, the output from a command is displayed in a separate window, but it disappears immediately.

5. The OneCommand Manager application does not display the OS Device Name for LUNs attached to vPorts. ([BZ 146718 Keep](#))

In the **LUN Information** tab, under **Mapping Information**, the **OS Device Name** field displays **N/A** instead of the device name. All other information on the **LUN Information** tab is displayed correctly.

6. When you install the OneCommand Manager application on a guest operating system, answers to the installer prompts are ignored. ([BZ 137136/BZ 137340/BZ 52476/BZ 137408 Keep](#))

When you install the OneCommand Manager application on a guest operating system, you are presented with management mode options (for example, local only, full-management, read-only, and so on). Answers to these questions are ignored; all installations on guest operating systems are set to local mode, read-only, and remote management.

7. Boot from a storage area network (SAN) is not available using the Common Information Model (CIM) interface with the OneCommand Manager application GUI or CLI.
8. When you manage a host using the CIM interface and you initiate a batch download process, all the adapters of the CIM-managed host are displayed because the required validation logic is not available in the CIM Provider.

#### Workaround

Manually deselect the adapters you do not want included in the batch download before starting the download. If you start the download without deselecting the non-matching adapters, the firmware download is initiated and results in an error for non-matching adapters.

9. When you start the OneCommand Manager application on a Windows Server 2012 R2 system, the popup message `Publisher is unknown` is displayed.

This message indicates that the publisher is unknown, and you are prompted to allow the program to make changes to the computer.

#### Workaround

Do one of the following:

- Click **Yes** on the popup message to run the OneCommand Manager application.
- Disable the popup by setting the **User Account Control** settings to **Never Notify**.
- Disable the popup by performing the following steps:
  - a. Select **Start > Run**, type `secpol.msc`, and click **OK**.
  - b. Double-click **Local Policies**.
  - c. Double-click **Security Options**.
  - d. Double-click **User Account Control: Behavior of the elevation prompt for administrators in Admin Approval Mode**.
  - e. Select **Elevate without prompting**.
  - f. Click **OK**.

10. A set link speed issue occurs after an SFP hot swap.

LPe16000-series adapters do not support SFP hot swap if the replacement SFP is not the same model as the original SFP. Two consequences occur in the OneCommand Manager application:

- The **Port Attributes** tab in the OneCommand Manager application or the OneCommand Manager CLI `PortAttributes` command might display incorrect data for the **Supported Link Speeds** attribute. This issue is cosmetic.
- Boot from SAN Management might be unable to set the `Boot Code Link Speed` parameter to 16 Gb/s.

**Workaround**

After changing the SFP, reset the LPe16000 port or reboot the server.

11. If an adapter is disabled when you attempt to save the DCB settings, the DCB settings are not saved. ([BZ 149048 Keep won't fix](#))

**Workaround**

Ensure that the adapters are enabled.

12. When using an Internet Explorer 11 browser, navigating to the **Index** or **Search** pages in the online help results in those pages being blank.

**Workaround**

Click **Contents** and refresh the browser, or load the help URL in a different browser.

13. On an ESXi host, when FA-PWWN is enabled or disabled and an adapter port is reset using the `esxcli elxmgmt` plugin, operations performed on the adapter using the OneCommand Manager application might not work as expected. ([BZ 206812/BZ 207145 Keep](#))

**Workaround**

To discover the adapter ports with the new WWPN, restart the Small-Footprint CIM Broker (SFCB) on the ESXi host and refresh the OneCommand Manager application.

14. If the CLI (HBACMD) is used to perform a firmware download to a local adapter, and the OneCommand Manager GUI is running while that firmware download is occurring, the OneCommand Manager GUI might experience problems displaying information on various display tabs after the download is completed. The value displayed for most of the fields on the affected tabs or dialogs is N/A. ([BZ 191905 aged-out](#))

**Workaround**

Do one of the following:

- When a firmware download has been performed by using the OneCommand Manager CLI, if N/A is shown for most of the OneCommand Manager GUI display fields, exit the GUI, and then restart it. The fields are displayed correctly.
- Ensure that the OneCommand Manager GUI is stopped or is not running prior to performing a firmware download using the OneCommand Manager CLI.
- Perform the firmware download using the OneCommand Manager GUI instead of the CLI.

15. LPe31000-series and LPe32000-series adapters might experience a link-down condition after running a cable link diagnostics test when they are connected to Brocade switches running Fabric OS (FOS) versions prior to v8.1.2. ([BZ 205782/BZ 207515 Keep](#))

**Workaround**

Manually reset the switch port using the `portdporttest --exit` command.

16. Roles-based Secure Management mode is available.

Secure Management mode is a roles-based security implementation. During the OneCommand Manager application installation, you are asked if you want to run in Secure Management mode. When the OneCommand Manager application is installed in this mode, the following operational changes occur:

- A non root or non administrator user can run the OneCommand Manager application.
- The OneCommand Manager application host uses a user's credentials for authentication.

- A user has OneCommand Manager application configuration privileges according to the OneCommand Manager application group to which the user is assigned.
- In Secure Management mode, a root or administrator user is provided full privileges on the local machine (OneCommand CLI does not require credentials) but no remote privileges.

**NOTE:** Refer to the *Emulex OneCommand Manager Application for LightPulse® Adapters User Guide* for additional information on Secure Management mode.

17. OneCommand Manager Secure Management mode requires OneCommand Manager user groups to be configured on the domain or, if the host is not running on a domain, on the host machine.

OneCommand Manager Secure Management must be able to get the OneCommand Manager application group to which the user belongs from the host's domain (Active Directory or LDAP) or, if the host is not part of a domain, the host's local user accounts. This access is associated with user groups, not with specific users. Administrators set up user accounts such that a user belongs to one of these four OneCommand Manager application user groups.

**Table 3: Secure Management User Privileges**

User Group	OneCommand Manager Capability
ocmadmin	Allows full active management of local and remote adapters.
ocmlocaladmin	Permits full active management of local adapters only.
ocmuser	Permits read-only access of local and remote adapters.
ocmlocaluser	Permits read-only access of local adapters.

These four groups must be created and configured on the host machine or network domain. OneCommand Manager Secure Management uses the C-library API calls `getgrnam` and `getgrid` to retrieve the OneCommand Manager Secure Management group information. The equivalent to these can be obtained on the shell command line by typing the `getent group` command. If the four OneCommand Manager application groups are listed, along with their member users, this is an indication that the host machine is sufficiently configured to work with OneCommand Manager Secure Management.

18. To view online help using the Google Chrome browser, you must disable Chrome's security check using the `--allow-file-access-from-files` option:
- a. Create a copy of the Chrome shortcut on the desktop, and rename it to RH Chrome L.
  - b. Right-click the new **Chrome** icon and select **Properties**.
  - c. Add the `--allow-file-access-from-files` text to the end of the path appearing in the target. You must leave a space between the original string and the tag you are adding.
  - d. Click **OK** to save your settings. Close any open instances of Chrome.
  - e. To open a local copy of the online help, either use the new shortcut to open Chrome, and then press **Ctrl + Open** and browse to the start page; or open Chrome with the new shortcut, and then right-click the start page and click **Open With > Google Chrome**.
19. The 32-bit or 64-bit `libcurl` file is required and must be copied to the Windows system when downloading firmware using http or https services with the WMI CIM Studio tool. ([BZ 199741 Keep won't fix](#))
20. To manage a remote ESXi 6.5 host using the OneCommand Manager application, set the configuration parameter `enableSSLv3` to `true` in the SFCB configuration file (`/etc/sfcb/sfcb.cfg`). By default, this parameter is not present in the configuration. ([BZ 194196/BZ 194247 Keep. Release noted](#))
- To add or update the `enableSSLv3` parameter, perform these steps:
- a. Stop the `sfcb-watchdog` application. Type the following command:

```
etc/init.d/sfcbd-watchdog stop
```

b. Add or update the following lines in the `/etc/sfcb/sfcb.cfg` file:

```
enableSSLv3:    true
```

```
sslCipherList: HIGH
```

c. Start the `sfcb-watchdog` application. Type the following command:

```
etc/init.d/sfcbd-watchdog start
```

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, the A logo, Brocade, ClearLink, Emulex, ExpressLane, LightPulse, OneCommand, and OneConnect are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries, and/or the EU.

Copyright © 2015–2018 Broadcom. All Rights Reserved.

The term “Broadcom” refers to Broadcom Inc. and/or its subsidiaries. For more information, please visit [www.broadcom.com](http://www.broadcom.com).

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.