

Error Message Resolution: OneCommand Manager for VMware vCenter Plug-in v1.1 reports "User does not have enough privileges to register an extension"

Problem:

After installing the Emulex OneCommand Manager for VMware vCenter v1.1, you need to register the plug-in. When you try to do this, you get an error message, as shown below in Example 1:

	OneCommand [™] for VMware VCenter
User does	not have enough privileges to register an extension.
	ок
HTTPS Port	
Username	
Password	
OCM Plug-in Server Name	10.192.90.123
Reset	Register Unregister

Example 1: Error message while registering OneCommand Manager plug-in v1.1



Resolution:

Log into the vCenter Server with the Administrator account and note the following: 'Administrator' user and 'Administrator' role are two separate entities. When viewing the Permissions Tab for the Datacenter created, we see only the Administrator group but no Administrator role assigned. In order to register the plug-in you will need to explicitly add the 'Administrator' user with 'Administrator' privileges. The same holds true when you add a user with a different name. Use the following steps to add the Administrator user to the Administrator role and to add a user with the correct privileges to register the plug-in.

- 1. Select the Datacenter in the tree.
- 2. Go to the Permissions Tab.
- 3. Right click on DataCenter and select Add Permission or use Ctrl-P.
- 4. Select Add.
- 5. Next select from the 'Users and Group' the name Administrator.
- 6. Change the Assigned Role from the drop down menu to Administrator.
- 7. Select OK and exit the pop-up.
- 8. Next, select OK to exit the 'Assign Permissions' window.
- 9. Register the plug-in.

Adding a User

Log into vCenter Server and check the role for the user in vCenter Server. When adding a user through vCenter Server, it defaults to a read-only role. Then verify the following options:

- 1. If the current user has a custom role, make sure that the required privileges to register the extension and access the OCM for VMware. Refer to the snapshot from the user manual in this document to know the required privileges. And refer vCenter Server manual for assigning privileges for a role.
- 2. Assign 'Administrator' role to the user which, by default, has the "read only" privilege assigned. Example 1 and Example 2 below illustrate this.



File Edit View	Inventory Administrat	ion Plug-ins Help					
	🟠 Home 🕨 🛃 Inve	ntory 🕨 🎁 Hosts and Clu	isters			😴 🕶 Search Inventory	Q
d 🗗 🖉	す器			Change the role from	<u>`</u>		
🛃 VCENTER	5	TechMkt		Read Only			
E 📙 Cost	aMesa erhMkt	Getting Started Summary	Virtual Machines Hosts Res	ource Allocation Perf mance Task	s & Events Alarms Permiss	ions Maps Profile Compliance Stora	ige Views 🛛 🕼
	00.012.00.124 (mair	User/Group	Role	Defined in		· · · · ·	
	UD.052.50.220	Administrator	Administrator				
	Win2k8r2-VM	acm 2	Read-only	CostaMesa			
	D.1782.00.1124		Administrator				
	B.1782.90.129	😤 Administrators	Administrator	VCENTER5			
	HS22-BL2-Portal.tec						
	uda20-build17 vCenter Server 4						
	vSphere Managemer						
cent Tasks					Name, Targ	et or Status contains: +	Clear
ame	Target	Status	Details	Initiated by	vCenter Server	Requested Start Ti 🗢 Start Time	
Tasks 🞯	Alama					License Period: 172 days remaining	

Example 1: The user's default role shows "Read-only"



VCENTER5 - vS	ohere Client nventory Administra	tion Diverties Liefs						_ 🗆 ×
							Search Inventory	
	Home P 💦 Inve	entory 🕨 🎁 Hosts and Clus	ters		Role. Close the		Search Inventory	Q
5 (* 11)				client and la make sure y	unch again to			
VCENTER5		10.192.91.220 ¥Mware E5	Xi, 5.0.0, 456551	make sure y	ou can login.			
🖂 🏨 Ted	hMkt	Getting Started Summary	-)	nce Configuration	Alarms	Permissions Maps	Storage Views Hardware Status Er	mulex OneCom \land 🕨
2	10.192.90.124 (mair 10.192.91.220	User/Group	Role		Defined in			
	Win2k8r2-VM	Administrator Ocm	Administr Administr		TechMkt CostaMesa			
	192.90.126 192.91.124	aamaya	Administr		CostaMesa			
😑 🥱 10.3	192.91.128							
- B	H522-BL2-Portal.tec							
	uda20-build17 vCenter Server 4							
	vCenter Server 5							
a	v5phere Managemer							
cent Tasks						Name, Targe	t or Status contains: -	Clear >
ame	Target	Status	Details	Initiated by		vCenter Server	Requested Start Ti 🖙 Start Time	• O
								<u> </u>
🔁 Tasks 🞯 Al	arms							ocm //

Example 2: Here, the user has been changed to Administrator:

Now, launch the Registration shortcut link from the desktop, as shown below:



Next, register the plug-in, as shown in Example 3:



One MF	Command [™] for VMware NAGER vCenter
∨Center Ser∨er Name	
vCenter Server HTTPS Port	443
Username	
Password	
OCM Plug-in Ser∨er Name	10.192.90.127
Reset	Register Unregister
X	MULEX

Example 3: This is the screen you will see to register the plug-in.

If, for some reason you get an error message saying "Unable to register OCM for VMware vCenter", check the Windows account type in Windows 2003/2008/7 to ensure it is not set for Standard user. You will need to change the user from Standard to Administrator and try again to register the plug-in. A screenshot with this error message is shown in Example 4:



OneCommand [™] for VMware MANAGER vCenter
vCenter Server
vCenter Server
Message from webpage 🛛 🛛 🗙
Unable to register OCM for VMware vCenter. Please check if the IP Address is reachable from vCenter Server or choose another IP Address from the listed options.
OK
Reset Register Unregister

Example 4: If you get this error message, change the user from Standard to Administrator and try again to register the plug-in.

For additional information, Example 5 is a screenshot from the OneCommand Manager vCenter Plug-In User's Manual for Active Directory (page 18: <u>http://www-</u> dl.emulex.com/support/vmware/vcenter/110/vcenter_user_manual.pdf)

Application Note



Behavior of OCM for VMware vCenter for Settings in the ESX Server

Active Directory Feature

Refer to the vSphere manual on the VMware website for information on creating a user with required privileges and changing access permissions for a user in the Active Directory.

Only a user with these specific privileges can read and perform active management in OCM for VMware vCenter:

- · "Host.CIM.CIM Interaction" to read data through the OCM for VMware vCenter
- "Host.CIM.CIM Interaction" and Host.Configuration.Maintenance" to perform any active management of the Emulex adapters
- · "Extension.Register extension" to register OCM for VMware vCenter using the registration utility
- "Extension.Unregister extension" to unregister OCM for VMware vCenter using the registration utility

All other users including the root user of the ESX host cannot perform any actions including reading data. If a user without the required privileges attempts to perform any action in OCM for VMware vCenter, an error message is displayed.

Example 5: OneCommand Manager vCenter Plug-In User's Manual for Active Directory

Application Note







www.emulex.com

World Headquarters 3333 Susan Street, Costa Mesa, California 92626 +1 714 662 5600 Bangalore, India +91 80 40156789 | Beijing, China +86 10 68499547 Dublin, Ireland+35 3 (0)1 652 1700 | Munich, Germany +49 (0) 89 97007 177 Paris, France +33 (0) 158 580 022 | Tokyo, Japan +81 3 5322 1348 Wokingham, United Kingdom +44 (0) 118 977 2929