



Storage Adapter

Toxic/Hazardous Substances and Elements Table | 有毒有害物质或元素名称及含量标识

Toxic and Hazardous Substances or Elements   有毒有害物质或元素						
部件名称 Product Name	铅 Lead (Pb)	汞 Mercury (Hg)	镉 Cadmium (Cd)	六价铬 Hexavalent Chromium (Cr6+)	多溴联苯 PolyBrominated Biphenyls (PBB)	多溴二苯醚 PolyBrominated Diphenyl Ethers (PBDE)
存储适配器 Storage Adapter	X	O	O	O	O	O

O: 表示该有毒有害物质在该部件所有均质材料中的含量均在SJ/T11363-2006规定的限量要求以下

O: Indicates that the content of the toxic and hazardous substances in all the homogeneous materials of the part is below the concentration limit requirement as described in SJ/T 11363-2006.

X: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006规定的限量要求

X: Indicates that the content of the toxic and hazardous substances in at least one homogeneous material of the part exceeds the concentration limit requirement as described in SJ/T 11363-2006.

“10” = □ 环保使用周期 : Environmental Protection Use Period

For use only with compatible UL-listed servers that have installation instructions detailing the user installation of the card cage accessories.

California Proposition 65 Notice

**WARNING:** This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Board Handling**

Adhere to the following guidelines:

- Perform all installation work at an electrostatic discharge (ESD) -safe workstation that meets EIA-625, *Requirements for Handling Electrostatic-Discharge-Sensitive (ESDS) Devices*. Perform all actions in accordance to the latest revision of the IPC-A-610 ESD-recommended practices.
- To avoid the risk of data loss, back up your data before you change your system configuration.
- Disconnect the system from the power supply and from any networks to which you will install the product, or you risk damaging the system or experiencing electrical shock.
- CacheVault™ power modules (SuperCaps) are not hot-pluggable. Remove power from the card prior to attaching a CacheVault power module.
- When installing an adapter, press down evenly on the top corners of the base board. Avoid contact with the brackets, heat sinks, or any installed daughter cards. Any stress that exceeds 500 micro-strain, or 500 micro inches, of deflection per inch of board material in any direction could damage the board.

**ATTENTION:** Provide sufficient airflow to the adapter. Refer to the product user guide, available in the Support Documents and Download center, for adapter airflow requirements.

**Additional Product Information**

Visit the product pages or the Support Documents and Downloads center to access all product documentation, latest firmware, and latest drivers. Refer to the appropriate product quick installation guide or user guide for bracket replacement instructions, detailed installation instructions, and storage guidelines. Use the following links to find your product:

- Navigate to a specific product: <https://www.broadcom.com/products/storage/>
- Search for a specific product or document: <https://www.broadcom.com/support/download-search>

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, the A logo, and CacheVault are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries, and/or the EU.

Copyright © 2016–2019 Broadcom. All Rights Reserved.

The term "Broadcom" refers to Broadcom Inc. and/or its subsidiaries. For more information, please visit [www.broadcom.com](http://www.broadcom.com).

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.



28226-00F