

## Product Brief



### Applications

- Server and external storage
- Direct-attached SAS/SATA/NVMe ROC solutions
- SAS RAID host bus adapter (HBA)
- PCIe-attached SSDs with industry-leading device management and error recovery

### Key Features

- High-performance I/O processor
- Dual-core Arm A15 at 1.6 GHz
  - 32-KB L1 I/D caches
  - 2-MB shared L2 cache
  - 15-MB on-chip memory
- PCI 16/24 PHY SAS/SATA/PCIe interface: 24-, 12-, 6-Gb/s SAS; 6-Gb/s SATA
- HW secure boot and attestation
- XOR DMA Engine for RAID 5 and 6
- RAID features:
  - MegaRAID™ support with activation key
  - RAID levels: 0, 1, 5, 6, 10, 50, 60
- DRAM backup at power fail using Open NAND Flash Interface (ONFI): Supports bad block management
- x16 Tri-Mode (SAS3/SATA3/PCIe4) PCI device port configurations: 1x16, 8x2, 4x4, 2x8, and 16x1
- Supports 22.5-, 12-, and 6-Gb/s SAS and 6-Gb/s SATA data transfer rates
  - Spread spectrum clocking
  - Supports the SSP, SMP, STP, and SATA protocols
  - Supports narrow and wide SAS ports

# SAS4116W Tri-Mode RAID-on-Chip PCIe 4.0 x16, 16-Port 24G SAS/ SATA/NVMe ROC Solution

## High-Performance ROC Features Tri-Mode SerDes Technology, NVMe Connectivity, and a High-Speed DDR4 Memory Interface

### Broadcom Storage

Broadcom now enables high-performance 24G SAS, PCIe 4.0 storage connectivity, and flexible system designs to support NVMe, SAS, and SATA devices with its new family of SAS4100 Tri-Mode RAID-on-Chips (ROCs). Broadcom offers the industry's broadest portfolio of storage solutions, backed by decades of experience and trusted by the world's leading server and storage suppliers. Broadcom provides the building blocks for storage solutions that help customers understand, prioritize, store, and protect critical data.

### Overview

The SAS4116W, part of the eighth generation of SAS ROCs from Broadcom, is based on the industry-leading Fusion-MPT™ (message-passing technology) architecture and features Tri-Mode SerDes technology that enables seamless operation of up to 16 direct-connect NVMe, SAS, or SATA storage devices from any system design. This PCIe Gen 4.0 x16, 16-port 24G SAS ROC delivers game-changing performance over previous generations, with a 4.5x increase in RAID 5 Random Write IOPs and an over 2x increase in bandwidth.

The SAS4116W host interface supports 16-wide PCI Express (PCIe) lanes and complies with the PCIe 4.0 specification, offering up to 6.7 million Random Read IOPs and 1.1 million Random Write IOPs in RAID configurations. The ROC incorporates advanced security features such as attestation and hardware secure boot. Hardware secure boot, which permits only authenticated firmware to execute, enables the controller to boot from an internal boot ROM (IBR) to establish the initial Root of Trust (RoT). Hardware secure boot authenticates and builds a Chain of Trust (CoT) with succeeding software using this RoT (Implicit Trust). The SAS4116W ROC also supports attestation, the next generation in security (Explicit Trust).

The introduction of PCIe devices executing NVMe command sets to the existing SAS/SATA infrastructure makes industry-standard hot-pluggable drive bays even more versatile. The 16-port Tri-Mode ROC device interface provides SAS data transfer rates of 24, 12, and 6 Gb/s per lane, SATA data transfer rates of 6 Gb/s per lane, or PCIe data transfer rates of up to 16.0 GT/s per lane and is backward compatible with 5.0/2.5 GT/s. The ROC automatically negotiates between the speeds and protocols. A T-10 end-to-end data protection (EEDP) model for early detection of and recovery from data corruption and spread-spectrum clocking (SSC) for EMI reduction are supported. Additional features include SAS 2.1 power management and DataBolt2 technology, allowing users to take advantage of 24-Gb/s speeds while utilizing existing 12-Gb/s and 6-Gb/s drives and backplanes.

## Key Features (cont.)

- T10 end-to-end data protection (EEDP)
- Optical cable support
- SAS 2.1 power management
- Supports up to 240 SAS/SATA devices
- Supports DataBolt2 bandwidth aggregation technology
- Separate Refclk Independent SSC (SRIS)
- Supports up to 64 PCIe devices behind PCIe switches
- PCIe 4.0 host interface
  - Supports x16, x8, x4, x2, x1 PCIe lanes at a transfer rate up to 16.0 GT/s per lane, full duplex
  - Lane and polarity reversal
  - Supports end-to-end CRC (ECRC) and advanced error reporting (AER)
  - PCIe hot-plug support
  - Supports PCIe rate negotiation
- Advanced power management
  - Slumber and Partial power mode support for SAS and SATA devices
  - Programmable SAS link power down
- External memory interface support: SPI-based Flash ROM
- Communication Interfaces
  - I<sup>2</sup>C interfaces for enclosure management services
  - UART interface for debug
- SFF-8485 compliant, SGPIO
- Supports Universal Bay Management (UBM)
- JTAG support
- Package (estimated): 35 mm

## Overview (cont.)

The SAS4116W ROC integrates a 2×72-bit, high-speed DDR4 memory interface that delivers faster speeds at 3200 MT/s and enables higher RAID performance. The ROC is powered by a high-performance dual-core Arm A15, 1.6-GHz processor, featuring 32-KB L1 I/D caches, 2-MB shared L2 caches, and 15-MB on-chip memory.

The Broadcom ROC offers full-featured RAID implementation with an I/O acceleration (IOA) engine for infrastructure and framework to incorporate I/O and RAID function accelerators. In addition, the 4116W supports MegaRAID hardware RAID (0, 1, 5, 6, 10, 50, 60) and can support up to 240 SAS or SATA devices. It supports up to 16 direct-attached PCIe devices and complies with PCIe 4.0 specifications, PCIe dynamic power allocation (DPA), end-to-end cyclic redundancy check (ECRC), and advanced error reporting (AER) with compatible devices. The ROC also supports NVMe over PCIe to attached PCIe devices.

## Fusion-MPT Architecture Overview

Fusion-MPT architecture marks the next generation of I/O architecture designed to deliver the highest performance available today while reducing time to market, integration, and certification time. Fusion-MPT devices are high-performance, cost-effective protocol controllers that represent the newest system-level integration technology in intelligent I/O processors from Broadcom.